

IP 2503PA Plus is a white gloss polymeric vinyl featuring Spandex's "PerfectApply" technology and a permanent, solvent-based adhesive. This product has been especially created for digital printing on large-format inkjets suitable for printing with eco solvent and solvent inks as well as UV-cured and latex inks.

IP 2503PA Plus

IP 2503PA Plus features specific polymeric, non-migrating plasticizers and UV stabilizers, which ensure long-term outdoor durability and also incorporates Spandex's "PerfectApply", bubble-free technology to facilitate application. IP 2503PA Plus is intended for indoor and outdoor applications such as markings, decorations and vehicle graphics. It also incorporates a B1 fire rating. In order to ensure the best results, this product should be dry applied. Laminate: IP 2810-100, IP 2810-101, IP 2810-102, IP 2810-200, IP 2830-101, IP 2830-102, IP 2830-105, IP 2830-106, IP 2830-200.

Compatibility of environment (unprinted):

EN71-3 conform (heavy metal migration), EN ISO 11885 conform (heavy metal concentration), Phtalate RL 2005/84/EG / conform (REACH).

Specifications	
DESCRIPTION	Polymeric vinyl
COLOUR	White gloss
THICKNESS	70 μ
WEIGHT	N/A
ADHESIVE	Solvent acrylic permanent
ADHESIVE STRENGTH	20N / 25mm (Finat TM 1/24h)
RELEASE PAPER	PE-coated silicone paper, 140g/m ²
TEMPERATURE RANGE	-30°C to +90°C
DURABILITY (UNPRINTED)	7 years
FLAME RETARDANCY	B1
SHELF LIFE	2 years, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© January 2013 Spandex Group. Technical specifications subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.